IJIREEICE ISSN (O) 2321-2004, ISSN (P) 2321-5526

International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering

Impact Factor 8.414 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 14, Issue 10, October 2026

DOI: 10.17148/IJIREEICE.2026.141028

Smart Portable Automotive Glass Defogger: Automated Condensation Prevention Using ESP32, Environmental Telemetry, and Real-Time Mobile Dashboard Controls

Suyog Jitendra Danole[1], Pragati Raju Shinde[2], Shrutika Vishwanath Teke[3], Pranjal Anil Gurav[4]

Lecturer, Computer Science and Information Technology, Sharad Institute of Technology, Polytechnic, Yadrav, Ichalkaranji, India[1]

Student, Computer Science and Information Technology, Sharad Institute of Technology, Polytechnic, Yadrav, Ichalkaranji, India[2]

Student, Computer Science and Information Technology, Sharad Institute of Technology, Polytechnic, Yadrav, Ichalkaranji, India[3]

Student, Computer Science and Information Technology, Sharad Institute of Technology, Polytechnic, Yadrav, Ichalkaranji , India[4]

Abstract: Windshield fogging compromises road safety during rainy and cold seasons when cabin humidity crosses the dew point threshold [1]. This paper presents a portable, plug-and-play automotive glass defogger system governed by an ESP32 microcontroller that utilizes precision atmospheric telemetry and automatic heating algorithms for automated condensation prevention. The system operates with 100% autonomous operation and achieves an application telemetry latency of less than 3.0 seconds via real-time mobile dashboard controls. Experimental performance verification demonstrates rapid optical clearance within 35 seconds from heavy fog saturation, a 60% reduction in energy consumption compared to full vehicle air conditioning heating cycles, and safe operation from a standard 12V auxiliary socket drawing less than 8A [2].

Keywords: Automotive Glass Defogger, ESP32 Microcontroller, Blynk IoT, Magnus-Tetens Dew Point, DHT22 Sensor, PTC Ceramic Heater, Condensation Prevention.

I. INTRODUCTION

A. *Background and Context*

Automotive glass condensation presents significant operational and safety challenges under adverse weather conditions. Conventional manual defogging interventions require drivers to quickly open windows, set the heater to full before turning on the air conditioning (AC), turn down or switch off the AC intermittently, use the defrost vent without heat during winter, or rely on windshield wipers during summer until cabin and exterior temperatures balance. Standardizing defrosting and defogging performance across passenger vehicles has long been a focus of automotive engineering guidelines (SAE J953) [3], particularly as embedded safety and accident detection systems become increasingly vital for economical passenger vehicles [4].

B. *Core Motivation*

The development of an automated, portable defogging architecture addresses three primary limitations in existing passenger vehicles:

IJIREEICE ISSN (O) 2321-2004, ISSN (P) 2321-5526

International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering

Impact Factor 8.414 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 14, Issue 10, October 2026

DOI: 10.17148/IJIREEICE.2026.141028

- **Impaired Visibility:** Windshield condensation is a major hazard that causes severe roadway accidents during adverse weather conditions. Prior automotive safety research highlights the necessity of proactive sensor-driven interventions to prevent accidents in economical cars [4], [7].
- **HVAC Inefficiency:** Factory air conditioning systems consume excessive fuel and engine horsepower during defogging cycles. Optimizing auxiliary loads is critical to preserving engine performance in economical passenger vehicles [7].
- **Universal Portability:** Older legacy passenger vehicles frequently lack rear or front automatic defogging capabilities and require a retrofit solution.

II. LITERATURE REVIEWAND PRIOR ART

Existing automotive defogging methods rely on manual heating, ventilation, and air conditioning (HVAC) manipulation, printed resistive grids, or chemical coatings. In the broader domain of automotive embedded systems for economical vehicles, researchers have demonstrated the effectiveness of microcontroller-based architectures utilizing temperature sensors, shock sensors, GSM/GPS modules, and motor drivers to enhance road safety and optimize engine performance without requiring costly factory hardware [4], [7]. Furthermore, recent advancements in cloud-integrated smart networks [6] and intelligent power scheduling with interference management in wireless networks [5] provide a strong foundation for designing low-latency, energy-efficient IoT telemetry systems in vehicular environments. Table I compares conventional defogging approaches against the proposed embedded IoT system.

TABLE I: COMPARISON OF EXISTING DEFOGGING APPROACHES AND THE PROPOSED SYSTEM

Approach	Mechanism	Key Limitations	Proposed System
Manual HVAC	Driver activates blower and compressor	Distracts driver; high energy consumption	Autonomous trigger
Resistive Grid	Printed conductive lines on glass	Rear window only; fragile lines break	Front & side portable
Chemical Coatings	Hydrophilic spray films	Degrades quickly; creates night glare	Zero chemical residue

III. THEORETICAL FOUNDATION AND CORE ALGORITHM

A. *Magnus-Tetens Dew Point Estimation*

To prevent condensation proactively, the system estimates the cabin dew point temperature (T_{dew}) using the Magnus-Tetens formula [1], which approximates the dew point with an accuracy of ±0.35°C across cabin conditions. Given the measured cabin temperature (T) and relative humidity (RH), the intermediate parameter $\gamma(T, RH)$ and the dew point temperature T_{dew} are computed as follows:

$$\Gamma(T, RH) = (17.27 \cdot T) / (237.7 + T) + \ln(RH/100) \quad (1)$$

$$T_{dew} = (237.7 \cdot \gamma) / (17.27 - \gamma) \quad (2)$$

B. *Control Thresholds and Hysteresis Logic*

Rather than waiting for visible condensation to obstruct the windshield, the control algorithm employs two switching boundaries:

- **Predictive Triggering:** The system automatically engages the heating and airflow actuators when the glass temperature approaches within 2.5°C ofthe calculated dew point.
- **Hysteresis Safety Gate:** To prevent rapid relay or actuator chattering, the system deactivates only after the cabin relative humidity (RH) drops below 60% and the temperature margin exceeds 4.5°C.

IJIREEICE ISSN (O) 2321-2004, ISSN (P) 2321-5526

International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering

Impact Factor 8.414 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 14, Issue 10, October 2026

DOI: 10.17148/IJIREEICE.2026.141028

IV. SYSTEM ARCHITECTURE AND HARDWARE SPECIFICATIONS

A. *Hardware Block Architecture*

The system architecture is centered around an ESP32 NodeMCU central hub [2], which executes the dew point algorithm, generates pulse-width modulation (PWM) signals, and manages wireless communication over Wi-Fi and Bluetooth Low Energy (BLE). Efficient power allocation and reliable wireless connectivity are critical in dynamic mobile environments to minimize latency and energy consumption [5]. The peripheral subsystems interface with the central hub as follows:

- **Atmospheric Sensing:** A DHT22 sensor measures cabin temperature and relative humidity (RH) and feeds environmental telemetry to the ESP32 NodeMCU.
- **Power Supply:** A 12V DC car cigarette lighter socket supplies primary power to the system.
- **Thermal and Airflow Actuation:** The ESP32 controls a 12V Positive Temperature Coefficient (PTC) ceramic heating core and a centrifugal blower acting as an air diffuser via MOSFET drivers.
- **Bi-Directional Mobile Link:** The ESP32 communicates bi-directionally with the Blynk Mobile platform for user interface (UI) telemetry display and manual override commands.

B. *Bill ofMaterials and Component Specifications*

The hardware implementation utilizes off-the-shelf embedded and thermal components detailed in Table II.

TABLE II: HARDWARE COMPONENT SPECIFICATIONS AND FUNCTIONAL ROLES

Component	Rating / Specification	Functional Role
ESP32 Dev Board	Dual Core 240MHz, 3.3V Logic	Processing & IoT
DHT22 Sensor	−40 to 80°C, 0-100% RH	Atmospheric Input
PTC Air Heater	12V DC, 80W Self-Regulating	Defog Thermal Power
Centrifugal Fan	12V DC Blower, 15 CFM	Directed Air Curtain
LM2596 Buck Module	12V input → 5V 3A output	Step-Down Regulation

V. SOFTWARE EXECUTION AND HUMAN-MACHINE INTERFACE

A. *Software Logic Flowchart*

The embedded firmware executes a continuous five-stage control loop to monitor cabin conditions and manage defogging actuation:

- **Step 1 — Sample Sensors:** Poll cabin temperature and relative humidity via the DHT22 sensor every 2 seconds.
- **Step 2 — Compute T_{dew}:** Evaluate the Magnus-Tetens dew point formula using the sampled telemetry.
- **Step 3 — Check Override:** Check whether Manual Mode is active on the Blynk mobile application.
- **Step 4 — Trigger Actuators:** Switch the PTC ceramic heater and centrifugal fan MOSFET drivers based on the predictive dew point logic or manual override state.
- **Step 5 — Sync Telemetry:** Update the virtual pins on the smartphone dashboard.

B. *Mobile Dashboard and Telemetry Interface*

The Human-Machine Interface (HMI) is implemented on the Blynk IoT platform, maintaining an application telemetry latency of under 3.0 seconds. Leveraging cloud-synchronized telemetry architectures [6] and low-delay wireless transmission strategies [5], the mobile dashboard provides three core capabilities:

- **Real-Time Gauges:** Displays live cabin temperature, relative humidity, and computed dew point metrics.
- **Auto/Manual Switch:** Provides the driver with full override capability to force-activate or deactivate the heaters.
- **Early Warning Alerts:** Sends push notifications to alert users before the windshield glass reaches the saturation state.

Table III illustrates the virtual pin datastream mapping and sample operational telemetry on the Blynk interface.

IJIREEICE ISSN (O) 2321-2004, ISSN (P) 2321-5526

International Journal of Innovative Research in Electrical, Electronics, Instrumentation and Control Engineering

Impact Factor 8.414 ⁜ Peer-reviewed & Refereed journal ⁜ Vol. 14, Issue 10, October 2026

DOI: 10.17148/IJIREEICE.2026.141028

TABLE III: BLYNK VIRTUAL PIN DATASTREAMS AND SAMPLE OPERATIONAL TELEMETRY

Virtual Pin	Parameter Name	Sample Telemetry Value
V0	Cabin Temp	24.5 °C
V1	Humidity	78.2 %
V2	Dew Point	20.4 °C
V5	Status	DEFOGGING

VI. PERFORMANCE VERIFICATION AND EXPERIMENTAL BENEFITS

Testing of the prototype confirmed the system's operational efficiency and electrical compatibility across key automotive metrics:

- **Rapid Clearance Time (35s):** Restores complete windshield optical clarity within 35 seconds from heavy fog saturation.
- **Energy Savings (60%):** Achieves a 60% reduction in power draw compared to running full automotive AC heating cycles. This reduction in auxiliary electrical and compressor load aligns with broader efforts to optimize engine performance and fuel economy in economical passenger vehicles [7].
- **Standard Socket Power (12V):** Operates directly from a standard 12V vehicle accessory socket while drawing a safe current ofless than 8A, remaining well within common auxiliary accessory fuse limits.
- **Autonomous and Low-Latency Control:** Achieves 100% autonomous operation with less than 3.0 seconds ofmobile application telemetry latency.

VII. CONCLUSION AND FUTURE SCOPE

A. *Key Achievements*

The proposed project successfully demonstrates a functional IoT defogger utilizing proactive predictive triggering to prevent windshield condensation before saturation occurs. It integrates seamless mobile telemetry and manual safety override capabilities via the Blynk IoT platform into a universal, portable hardware unit suitable for retrofitting legacy automotive platforms without leaving chemical residue or obstructing visibility.

B. *Future Enhancements*

- **Direct Glass Temperature Sensing:** Incorporate an MLX90614 contactless infrared (IR) sensor to measure windshield glass surface temperature directly.
- **Vehicle Bus and Multi-Sensor Integration:** Implement Controller Area Network (CAN) bus integration to automatically synchronize the defogger with native vehicle telemetry, allowing unified operation alongside onboard accident detection modules [4] and driver health and engine performance optimization systems [7]. Future iterations can also incorporate deep learning models such as optimized Bidirectional Long Short-Term Memory (BiLSTM) networks for predictive power scheduling across vehicular sensors [5].
- **Aerodynamic Nozzle Optimization and Cloud Manufacturing:** Design and fabricate a 3D-printed custom aerodynamic duckbill diffuser nozzle to further optimize the directed air curtain across the glass, utilizing cloud manufacturing frameworks for scalable, smart, and sustainable production of custom automotive retrofit enclosures [6].

ACKNOWLEDGMENT

The heading of the Acknowledgment section and the References section must not be numbered. Causal Productions wishes to acknowledge Michael Shell and other contributors for developing and maintaining the IEEE LaTeX style files which have been used in the preparation of this template.

DOI: 10.17148/IJIREEICE.2026.141028

REFERENCES

[1]. G. Magnus, "Versuche über die Spannkräfte des Wasserdampfs," *Annalen der Physik*, vol. 137, no. 2, pp. 225–247, 1844.

[2]. Espressif Systems, *ESP32 Series Datasheet and Hardware Reference Manual*, v4.1, 2023.

[3]. Society of Automotive Engineers (SAE), *SAE J953: Passenger Car Windshield Defrosting and Defogging Systems*.

[4]. J. M. S. Mulla, D. Gavade, S. S. Bidwai, and S. S. Bidwai, "Research paper on airbag deployment and accident detection system for economic cars," in *2017 2nd International Conference for Convergence in Technology (I2CT)*, Mumbai, India, 2017, pp. 846–849, doi: 10.1109/I2CT.2017.8226248.

[5]. S. S. Mohite, U. D. Kolekar, J. S. Mulla, S. Bhakte, P. Shinde, and J. Patil, "Interference management and power scheduling in femtocell networks with the optimized power scheduling BiLSTM," *Computers and Electrical Engineering*, vol. 119, Part A, p. 109487, 2024, doi: 10.1016/j.compeleceng.2024.109487.

[6]. J. M. S. Mulla, S. S. Shirguppikar, P. B. Gavali, V. S. Ganachari, S. S. Patil, and S. I. Tamboli, "Cloud Manufacturing Implementation for Smart Manufacturing Networks," in *Smart and Sustainable Manufacturing*, S. Kunar, G. Mandal, P.S. Bahadur, S. Rama Sree, and M. Sreenivasa Reddy, Eds., 2026, ch. 21 , doi: 10.1002/9781394409334.ch21 .

[7]. J. M. Mulla, S. S. Magdum, S. S. Patil, S. S. Shirguppikar, S. B. Khot, and A. B. Chavan, "Engine Performance Optimization Using Driver Health Data for Economical Cars in the Indian Automotive Industry," in *2025 IEEE 4th International Conference for Advancement in Technology (ICONAT)*, Goa, India, 2025, pp. 1 –6, doi: 10.1109/ICONAT66879.2025.11 362830.

[8]. Visual Reference Sources: *www. alnahdhaauto. com* and *www. conrad. com*.